

SUN PROTECTION


LIFE BLACK-OUT 2028

Number	Colour	Width mm 2300	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
1029	white	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
9181	ice	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
1048	off white	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
2320	cream	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
2372	ivory	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
2371	mushroom	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
9090	grey	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63
9178	steel grey	✓	52%	0%	48%	49%	0%	51%	5-6	0,44	0,63

All printed colours and textures only provide orientation and are not reference pattern.

Usable for Pleated Blinds
 Colour Range 8
 Composition 100% PES
 Width 2300 mm
 Pleating Format 20 mm
 Cutting Process cold

Weight 280 g/m²
 Thickness 0,35 mm
 Damp room usable yes
 PVC free yes
 Halogen free yes
 OekoTex yes



D
black-out



suitable for
workstations



by Gerhard van Clewe
GmbH & Co.KG



Standard 100
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption · All light & solar properties have been tested internally or externally. · Gtot: measure total solar energy that passes through the glazing system and the fabric · FC-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g · Gtot and FC-value are calculated on the basis of a glass with an Ug-value of 1,6 and g-value of 0,7 according to DIN EN ISO 13363-1. · All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.