

SUN PROTECTION

VISTA 2059 / VISTA-REFLEX 2063

| Number | Colour | Width mm 2400 | Light Properties | | | Solar Properties | | | Light Fastness | Gtot - value | FC - value |
|--------|---------------|------------------|------------------|-----|-----|------------------|-----|-----|-------------------|-----------------|---------------|
| | | | R | T | A | R | T | A | | | |
| 1029 | white | | ✓ | 53% | 37% | 10% | 57% | 41% | 2% | 5-6 | 0,39 |
| 1048 | off white | | ✓ | 49% | 40% | 11% | 48% | 40% | 12% | 5-6 | 0,42 |
| 2428 | birch | | ✓ | 43% | 35% | 22% | 41% | 37% | 22% | 5-6 | 0,44 |
| 9234 | light grey | | ✓ | 36% | 30% | 34% | 35% | 29% | 36% | 5-6 | 0,46 |
| 1107 | milk | | ✓ | 44% | 42% | 14% | 41% | 40% | 19% | 5-6 | 0,44 |
| 4188 | pale lime | | ✓ | 38% | 34% | 28% | 36% | 35% | 29% | 5-6 | 0,46 |
| 9235 | mid grey | | ✓ | 28% | 29% | 43% | 29% | 30% | 41% | 5-6 | 0,48 |
| 9215 | silver lining | | ✓ | 31% | 28% | 41% | 30% | 28% | 42% | 5-6 | 0,48 |
| 5219 | sky blue | | ✓ | 42% | 36% | 22% | 39% | 34% | 27% | 5-6 | 0,45 |
| 9236 | steel grey | | ✓ | 14% | 12% | 74% | 15% | 14% | 71% | 5-6 | 0,52 |
| 2429 | latte | | ✓ | 30% | 24% | 46% | 34% | 27% | 39% | 5-6 | 0,46 |
| 8185 | soft purple | | ✓ | 36% | 30% | 34% | 31% | 31% | 38% | 5-6 | 0,47 |
| | | | | | | | | | | | |

| | | | | | | | | | | | |
|------|---------------|---|-----|-----|-----|-----|-----|-----|-----|------|------|
| 1029 | white | ✓ | 57% | 37% | 6% | 53% | 37% | 10% | 6-7 | 0,40 | 0,68 |
| 1048 | off white | ✓ | 55% | 37% | 8% | 53% | 38% | 9% | 6-7 | 0,40 | 0,68 |
| 2428 | birch | ✓ | 49% | 26% | 25% | 44% | 30% | 26% | 6-7 | 0,43 | 0,73 |
| 9234 | light grey | ✓ | 51% | 36% | 13% | 49% | 37% | 14% | 6-7 | 0,42 | 0,71 |
| 1107 | milk | ✓ | 50% | 33% | 17% | 45% | 30% | 25% | 6-7 | 0,43 | 0,73 |
| 4188 | pale lime | ✓ | 47% | 29% | 24% | 45% | 32% | 23% | 6-7 | 0,43 | 0,73 |
| 9235 | mid grey | ✓ | 47% | 21% | 32% | 43% | 23% | 34% | 6-7 | 0,43 | 0,73 |
| 9215 | silver lining | ✓ | 43% | 22% | 35% | 41% | 23% | 36% | 6-7 | 0,44 | 0,75 |
| 5219 | sky blue | ✓ | 48% | 32% | 20% | 47% | 32% | 21% | 6-7 | 0,42 | 0,71 |
| 9236 | steel grey | ✓ | 36% | 9% | 55% | 34% | 12% | 54% | 6-7 | 0,46 | 0,78 |
| 2429 | latte | ✓ | 49% | 20% | 31% | 48% | 23% | 29% | 6-7 | 0,42 | 0,71 |
| 8185 | soft purple | ✓ | 47% | 27% | 26% | 46% | 32% | 22% | 6-7 | 0,42 | 0,71 |
| | | | | | | | | | | | |

All printed colours and textures only provide orientation and are not reference pattern.

Usable for Pleated Blinds
 Colour Range 12 / 12
 Composition 100 % PES
 Width 2400 mm
 Cutting Process hot


Pleating Format 20 mm
 Weight 80 / 90 g/m²
 Thickness 0,15 / 0,17 mm
 Damp room usable yes
 PVC free yes
 OekoTex yes



Perlex



suitable for workstations



B semi-transparent



by Gerhard van Clewe GmbH & Co.KG



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.