

# SUN ○ PROTECTION

## CLASSIC BLACK-OUT-COLOUR 1161

Number	Colour	Width mm 2000	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
5205	lavender	✓	27%	0%	73%	22%	0%	78%	6-7	>0,40	>0,70
4169	ambrosia	✓	33%	0%	67%	30%	0%	70%	6-7	>0,40	>0,70
9202	feather gray	✓	42%	0%	58%	38%	0%	62%	6-7	>0,40	>0,70
2173	beige	✓	39%	0%	61%	37%	0%	63%	6-7	>0,40	>0,70
9199	flint grey	✓	21%	0%	79%	16%	0%	84%	6-7	>0,40	>0,70
2326	bleached sand	✓	40%	0%	60%	37%	0%	63%	6-7	>0,40	>0,70
9198	steel grey	✓	14%	0%	86%	9%	0%	91%	6-7	>0,40	>0,70
2400	linen	✓	31%	0%	69%	36%	0%	64%	6-7	>0,40	>0,70
9092	black	✓	9%	0%	91%	6%	0%	94%	6-7	>0,40	>0,70
9201	smoke grey	✓	26%	0%	74%	22%	0%	78%	6-7	>0,40	>0,70


All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Panel Track  
 Colour Range 10  
 Composition 100 % PES  
 Width 2000 mm  
 Cutting Process cold  
 Processing Direction warp & weft

Weight 290 g/m2  
 Thickness 0,45 mm  
 Moisture proofed yes  
 PVC free yes  
 Halogen free yes  
 OekoTex yes



suitable for  
workstations



D  
black-out



Standard 100  
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACh regulation.