

JUNO-REFLEX 1132

Number	Colour	Width mm 2300	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
1069	white	✓	68%	13%	19%	62%	16%	22%	5-6	0,39	0,56
2275	sand	✓	63%	9%	28%	55%	12%	33%	5-6	0,42	0,60
4139	spring green	✓	46%	5%	49%	42%	9%	49%	5-6	0,48	0,69
9154	light grey	✓	54%	12%	34%	52%	16%	32%	5-6	0,43	0,61
2276	brown	✓	38%	11%	51%	36%	14%	50%	5-6	0,51	0,73
5175	aqua	✓	29%	10%	61%	25%	15%	60%	5-6	0,56	0,80
9155	mid grey	✓	42%	9%	49%	39%	14%	47%	5-6	0,49	0,70
2294	nut	✓	23%	8%	69%	19%	13%	68%	5-6	0,58	0,83
9125	slate	✓	19%	9%	72%	18%	13%	69%	5-6	0,59	0,84
2295	chocolate	✓	33%	7%	60%	27%	11%	62%	5-6	0,55	0,79

All printed colours and textures only provide orientation and are not reference pattern.

Usable for  
Colour Range  
Composition  
Width  
Cutting Process  
Processing Direction

Roller / Pleated / Panel Track  
10  
100 % PES  
2300 mm  
cold  
warp

Weight  
Thickness  
Damp room usable  
PVC free  
Halogen free  
OekoTex


200 g/m<sup>2</sup>  
0,40 mm  
yes  
yes  
yes  
yes



Perlex



suitable for  
workstations



C  
dim-out



REACH-  
compliant



by Gerhard van Clewe  
GmbH & Co.KG



Standard 100  
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • FC-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and FC-value are calculated on the basis of a glass with an Ug-value of 1,6 and g-value of 0,7 according to DIN EN ISO 13363-1. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.