

SUN ○ PROTECTION

JUNO 1097

| Number | Colour | 89 | Width mm | | | Light Properties | | | Solar Properties | | | Light Fastness | Gtot - value | FC - value |
|--------|------------------|----|----------|------|------|------------------|-----|-----|------------------|-----|-----|----------------|--------------|------------|
| | | | 127 | 2300 | 3000 | R | T | A | R | T | A | | | |
| 1096 | silvery white | ✓ | ✓ | ✓ | - | 69% | 19% | 12% | 63% | 22% | 15% | 5-6 | >0,45 | >0,80 |
| 8170 | rose | ✓ | ✓ | ✓ | - | 42% | 10% | 48% | 23% | 15% | 62% | 5-6 | >0,45 | >0,80 |
| 4178 | peppermint | ✓ | ✓ | ✓ | - | 41% | 12% | 47% | 43% | 14% | 43% | 5-6 | >0,45 | >0,80 |
| 9158 | grey/black | ✓ | ✓ | ✓ | - | 25% | 15% | 60% | 20% | 18% | 62% | 5-6 | >0,45 | >0,80 |
| 8171 | orchid | ✓ | ✓ | ✓ | - | 49% | 15% | 36% | 44% | 18% | 38% | 5-6 | >0,45 | >0,80 |
| 4179 | soft-lime | ✓ | ✓ | ✓ | - | 52% | 20% | 28% | 32% | 24% | 44% | 5-6 | >0,45 | >0,80 |
| 9195 | silvery mid grey | ✓ | ✓ | ✓ | - | 18% | 13% | 69% | 14% | 17% | 69% | 5-6 | >0,45 | >0,80 |
| 8172 | berry | ✓ | ✓ | ✓ | - | 35% | 17% | 48% | 18% | 21% | 61% | 5-6 | >0,45 | >0,80 |
| 4139 | spring green | ✓ | ✓ | ✓ | ✓ | 45% | 16% | 39% | 41% | 19% | 40% | 5-6 | >0,45 | >0,80 |
| 8173 | aubergine | ✓ | ✓ | ✓ | - | 27% | 14% | 59% | 14% | 19% | 67% | 5-6 | >0,45 | >0,80 |
| 5175 | aqua | ✓ | ✓ | ✓ | - | 47% | 19% | 34% | 41% | 23% | 36% | 5-6 | >0,45 | >0,80 |
| 4140 | petrol | ✓ | ✓ | ✓ | - | 19% | 16% | 65% | 13% | 20% | 67% | 5-6 | >0,45 | >0,80 |
| 8134 | claret | ✓ | ✓ | ✓ | - | 24% | 15% | 61% | 18% | 19% | 63% | 5-6 | >0,45 | >0,80 |
| 5176 | night blue | ✓ | ✓ | ✓ | - | 18% | 12% | 70% | 13% | 16% | 71% | 5-6 | >0,45 | >0,80 |

All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Vertical / Pleated / Panel Track
 Colour Range 26 (14 / 12)
 Composition 100 % PES
 Width 89 / 127 / 2300 / 3000 mm
 Cutting Process hot
 Processing Direction warp


Weight 150 g/m2
 Thickness 0,35 mm
 Moisture proofed yes
 PVC free yes
 Halogen free yes
 OekoTex yes



Teflon



suitable for workstations



B semi-transparent



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACh regulation.