

sustainably finished by van Cleve

SUN PROTECTION




REVIVAL 1162

Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		89	127	2300	R	T	A	R	T	A			
9196	dust grey	✓	✓	✓	48%	34%	18%	45%	37%	18%	6-7	0,43	0,73
2323	sand	✓	✓	✓	37%	31%	32%	32%	35%	33%	6-7	0,47	0,80
9190	rock	✓	✓	✓	29%	27%	44%	25%	32%	43%	6-7	0,49	0,83
9197	iron	✓	✓	✓	11%	19%	70%	10%	22%	68%	6-7	0,54	0,92

Usable for Roller / Panel Track / Vertical
 Colour Range 4
 Composition 100% recycled PES
 Width 89 / 127 / 2300 mm
 Cutting Process cold
 Processing Direction warp

Weight 150 g/m²
 Thickness 0,35 mm
 Moisture proofed yes
 PVC free yes
 Halogen free yes
 OekoTex yes




REVIVAL BLACK-OUT 1045

Number	Colour	Width mm 2300	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
9196	dust grey	✓	67%	0%	33%	63%	0%	37%	6-7	0,36	0,61
2323	sand	✓	43%	0%	57%	44%	0%	56%	6-7	0,42	0,71
9190	rock	✓	24%	0%	76%	26%	0%	74%	6-7	0,48	0,81
9197	iron	✓	13%	0%	87%	11%	0%	89%	6-7	0,53	0,90

Usable for Roller / Panel Track / Vertical on request
 Colour Range 4
 Composition 100% recycled PES
 Width 2300 mm
 Cutting Process cold
 Processing Direction warp

Weight 290 g/m²
 Thickness 0,50 mm
 Moisture proofed yes
 PVC free yes
 Halogen free yes
 OekoTex yes



All printed colours and textures only provide orientation and are not reference pattern.

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.