

OPAL 1156


Number	Colour	2300 mm	Light Properties			Solar Properties			UV-Transmission	Openness factor	Gtot value	FC value	Darkening performance	Glare control	Night privacy	Visual contact with the outside	Control of solar gains
			R	T	A	R	T	A									
325	white	✓	47%	45%	8%	46%	45%	9%	-	-	0,43	0,73	0	1	1	2	1
1037	nature white	✓	45%	43%	12%	46%	44%	10%	-	-	0,43	0,73	0	1	1	2	1
327	grise	✓	36%	39%	25%	26%	42%	32%	-	-	0,49	0,83	0	1	1	2	1
2000	sand	✓	36%	45%	19%	34%	46%	20%	-	-	0,47	0,80	0	1	1	2	1
9225	mid grey	✓	27%	29%	44%	24%	37%	39%	-	-	0,50	0,85	0	1	1	3	0
4201	shadow lime	✓	31%	38%	31%	32%	40%	28%	-	-	0,47	0,80	0	1	1	2	1
9276	linen grey	✓	27%	32%	41%	26%	37%	37%	-	-	0,49	0,83	0	1	1	3	1
9150	iron	✓	16%	20%	64%	17%	36%	47%	-	-	0,52	0,88	0	1	1	3	0
9277	iron grey	✓	8%	16%	76%	9%	19%	72%	-	-	0,54	0,92	0	1	1	3	0
9084	black	✓	8%	12%	80%	4%	36%	60%	-	-	0,56	0,95	0	1	1	3	0

All printed colours and textures only provide orientation and are not reference pattern.

Revision 2

Usable for Roller Blinds, Vertical Blinds, Pleated Blinds, Panel Tracks
 Colour Range 10
 Composition 100 % PES
 Width 2300 mm
 Cutting Process hot
 Processing Direction warp & weft

Weight 140 g/m²
 Thickness 0,35 mm
 Damp room usable yes
 PVC free yes
 Halogen free yes
 OekoTex yes



R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.