SUN O PROTECTION

AMARANT 1123

Number	Colour	Width mm Light Properties 2800 R T A			Solar Properties R T A			Light Fastness	Gtot - value	FC - value	
1082	white	*	21%	58%	21%	15%	61%	24%	6-7	>0,55	>0,80
2338	nature	~	20%	52%	28%	16%	55%	29%	6-7	>0,55	>0,80
2339	cream		19%	50%	31%	14%	52%	34%	6-7	>0,55	>0,80

Usable for Roller / Panel Track
Colour Range 2
Composition 100 % PES
Width 2800 mm
Cutting Process hot
Processing Direction warp

All printed colours and textures only provide orientation and are not reference pattern.

Weight 100 g/m2
Thickness 0,50 mm
Moisture proofed yes
PVC free yes
Halogen free yes
OekoTex yes





OEKO-TEX®

transparent

Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes throught the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACh regulation.

