

sustainably finished by van Cleve

SUN ○ PROTECTION



RE-JUNO 1040

Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		89	127	2300	R	T	A	R	T	A			
1069	white	✓	✓	✓	69%	19%	12%	63%	22%	15%	5-6	0,37	0,63
2275	sand	✓	✓	✓	61%	16%	23%	56%	19%	25%	5-6	0,39	0,66
9154	light grey	✓	✓	✓	59%	14%	27%	52%	18%	30%	5-6	0,40	0,68
2276	brown	✓	✓	✓	42%	18%	40%	37%	21%	42%	5-6	0,45	0,76
9155	mid grey	✓	✓	✓	18%	13%	69%	14%	17%	69%	5-6	0,53	0,90
2294	nut	✓	✓	✓	44%	17%	39%	38%	20%	42%	5-6	0,45	0,76
9125	slate	✓	✓	✓	13%	11%	76%	10%	14%	76%	5-6	0,54	0,92
2295	chocolate	✓	✓	✓	27%	13%	60%	21%	17%	62%	5-6	0,50	0,85


All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Vertical / Pleated / Panel Track
 Colour Range 8
 Composition 100% PES (80% recycled PES)
 Width 89 / 127 / 2300 mm
 Cutting Process hot
 Processing Direction warp

Weight 150 g/m²
 Thickness 0,35 mm
 Moisture proofed yes
 PVC free yes
 Halogen free yes
 OekoTex yes



suitable for Workstations



B semi-transparent



by Gerhard van Cleve GmbH & Co.KG



Standard 100 by Oeko-Tex

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.