

TENDENCE BLACK-OUT 1118

Number	Colour	Width mm 2300	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
1072	snow	✓	78%	0%	22%	69%	0%	31%	6-7	0,35	0,50
2372	ivory	✓	54%	0%	46%	56%	0%	44%	6-7	0,41	0,59
9141	silver	✓	52%	0%	48%	48%	0%	52%	6-7	0,45	0,64
9215	silver lining	✓	53%	0%	47%	55%	0%	45%	6-7	0,41	0,59
9217	mid grey	✓	48%	0%	52%	52%	0%	48%	6-7	0,43	0,61
9216	flax	✓	26%	0%	74%	27%	0%	73%	6-7	0,54	0,77
9140	griffin	✓	9%	0%	91%	7%	0%	93%	6-7	0,63	0,90
2370	slime grey	✓	20%	0%	80%	19%	0%	81%	6-7	0,58	0,83
9084	clear black	✓	6%	0%	94%	4%	0%	96%	6-7	0,65	0,93
9175	dust grey	✓	12%	0%	88%	13%	0%	87%	6-7	0,61	0,87

All printed colours and textures only provide orientation and are not reference pattern.

Usable for
Colour Range
Composition
Width
Cutting Process
Processing Direction


Roller
10 (coloured back side)
100 % PES
2300 mm
cold
warp & weft

Weight
Thickness
Damp room usable
PVC free
Halogen free
OekoTex

270 g/m²
0,45 mm
yes
yes
yes
yes



suitable for
workstations



D
black-out



REACH-
compliant



by Gerhard van Clewe
GmbH & Co.KG



Standard 100
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption · All light & solar properties have been tested internally or externally. · Gtot: measure total solar energy that passes through the glazing system and the fabric · FC-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g · Gtot and FC-value are calculated on the basis of a glass with an Ug-value of 1,6 and g-value of 0,7 according to DIN EN ISO 13363-1. · All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.