

SUN PROTECTION

CLASSIC BLACK-OUT 1151

Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		2000	2300	3000	R	T	A	R	T	A			
1079	white	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
1098	antique white	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
4172	shadow green	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2398	cream pink	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2103	beige	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
5206	hawaiian ocean	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
4174	morning mist	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2173	wool beige	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
5207	imperial blue	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
9165	grey	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2326	bleached sand	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
5178	marine	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2400	linen	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
9200	silver lining	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
5205	lavender	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
9119	dark grey	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2399	nomad	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
8168	baton rouge	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
9092	black	✓	✓	✓	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
2401	chocolate	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46
8167	jester red	✓	-	-	84%	0%	16%	71%	0%	29%	6-7	0,33	0,46


All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Panel Track
 Colour Range 21
 Composition 100 % PES
 Width 2000 / 2300 / 3000 mm
 Cutting Process cold
 Processing Direction warp & weft

Weight 290 g/m2
 Thickness 0,45 mm
 Moisture proofed yes
 PVC free yes
 Halogen free yes
 OekoTex yes



suitable for workstations



D black-out



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACh regulation.