

JUNO BLACK-OUT 1112

Number	Colour	Width mm			Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
		89	127	2300	R	T	A	R	T	A			
1069	white	✓	✓	✓	64%	0%	36%	60%	0%	40%	6-7	0,39	0,56
2275	sand	✓	✓	✓	61%	0%	39%	56%	0%	44%	6-7	0,41	0,59
9154	light grey	✓	✓	✓	61%	0%	39%	57%	0%	43%	6-7	0,41	0,59
2276	brown	✓	✓	✓	26%	0%	74%	21%	0%	79%	6-7	0,57	0,81
9155	mid grey	✓	✓	✓	39%	0%	61%	36%	0%	64%	6-7	0,50	0,71
2294	nut	✓	✓	✓	25%	0%	75%	20%	0%	80%	6-7	0,57	0,81
9125	slate	✓	✓	✓	17%	0%	83%	14%	0%	86%	6-7	0,60	0,86
2295	chocolate	✓	✓	✓	19%	0%	81%	17%	0%	83%	6-7	0,59	0,84
5175	aqua	✓	✓	✓	43%	0%	57%	41%	0%	59%	6-7	0,48	0,69
4139	spring green	✓	✓	✓	47%	0%	53%	43%	0%	57%	6-7	0,47	0,67

All printed colours and textures only provide orientation and are not reference pattern.

Usable for
Colour Range
Composition
Width
Cutting Process
Processing Direction


Roller / Vertical / Panel Track
10 (coloured back side)
100 % PES
89 / 127 / 2300 mm
cold
warp

Weight
Thickness
Damp room usable
PVC free
Halogen free
OekoTex

320 g/m²
0,55 mm
yes
yes
yes
yes



suitable for
workstations



D
black-out



REACH-
compliant



by Gerhard van Cleve
GmbH & Co.KG



Standard 100
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,6 and g-value of 0,7 according to DIN EN ISO 13363-1. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.