

# SUN PROTECTION

## NEXUS 1098

Number	Colour	Width mm 3000	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
1120	white	✓	62%	30%	8%	65%	30%	5%	5-6	0,36	0,61
2463	sand shell	✓	49%	25%	26%	50%	26%	24%	5-6	0,41	0,69
9295	silver	✓	56%	23%	21%	58%	21%	21%	5-6	0,38	0,64
2464	oak brown	✓	38%	18%	44%	39%	20%	41%	5-6	0,44	0,75
9296	micro grey	✓	39%	20%	41%	45%	21%	34%	5-6	0,43	0,73
9297	brushed nickel	✓	25%	15%	60%	30%	19%	51%	5-6	0,47	0,80


All printed colours and textures only provide orientation and are not reference pattern.

Usable for Roller / Panel Track  
Vertical on request  
Colour Range 6  
Composition 100 % PES  
Width 3000 mm  
Cutting Process hot  
Processing Direction warp

Weight 150 g/m<sup>2</sup>  
Thickness 0,30 mm  
Moisture proofed yes  
PVC free yes  
Halogen free yes  
OekoTex yes



suitable for  
Workstations



B semi-  
transparent



by Gerhard van Clewe  
GmbH & Co.KG



Standard 100  
by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • Gtot and Fc-value are calculated on the basis of a glass with an Ug-value of 1,2 and g-value of 0,59 according to DIN EN 14501 glass C. • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.