

ANTARES BLACK-OUT COLOUR 1003

Number	Colour	Width mm				Light Properties			Solar Properties			Light Fastness	UV-Transm.	Gtot - value	FC - value
		89	127	2300	3000	R	T	A	R	T	A				
2025	beige	✓	✓	✓	✓	71%	0%	29%	68%	0%	32%	6-7	0%	0,36	0,51
2445	beach	✓	✓	✓	✓	51%	0%	49%	49%	0%	51%	6-7	0%	0,44	0,63
9124	light grey	✓	✓	✓	✓	66%	0%	34%	65%	0%	35%	6-7	0%	0,37	0,53
9037	manhattan	✓	✓	✓	✓	52%	0%	48%	52%	0%	48%	6-7	0%	0,43	0,61
9060	mouse grey	✓	✓	✓	✓	28%	0%	72%	26%	0%	74%	6-7	0%	0,55	0,79
9092	anthracite	✓	✓	✓	✓	5%	0%	95%	5%	0%	95%	6-7	0%	0,64	0,91

All printed colours and textures only provide orientation and are not reference pattern.

Usable for
Colour Range
Composition
Width
Cutting Process
Processing Direction

Roller / Vertical / Panel Track
6 (coloured back side)
100 % PES
89 / 127 / 2300 / 3000 mm
cold
warp & weft

Weight
Thickness
Damp room usable
PVC free
OekoTex

400 g/m²
0,45 mm
yes
yes
yes



Flame retardant

DIN 4102, B1
NF P 92-503-507,M1
BS 5867 part 2
UNI.8456-UNI.9174, C1
EN 13773
NFPA 701



suitable for workstations



D black-out



REACH-compliant



by Gerhard van Clewe GmbH & Co.KG



Standard 100 by Oeko-Tex®

R = Reflection, T = Transmission, A = Absorption · All light & solar properties have been tested internally or externally. · Gtot: measure total solar energy that passes through the glazing system and the fabric · FC-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g · Gtot and FC-value are calculated on the basis of a glass with an Ug-value of 1,6 and g-value of 0,7 according to DIN EN ISO 13363-1. · All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.