


OPAL-PRINT 2061 / 2062

Number	Colour	Width mm 2250	Light Properties			Solar Properties			Light Fastness	Gtot - value	FC - value
			R	T	A	R	T	A			
2061	2322-1037 safari*	✓	34%	47%	19%	33%	47%	20%	6-7	>0,40	>0,70
2061	9228-1037 slime grey*	✓	29%	30%	41%	28%	33%	39%	6-7	>0,40	>0,70
2061	9229-1037 shadow grey*	✓	13%	25%	62%	13%	28%	59%	6-7	>0,40	>0,70
2061	5218-1037 shadow blue*	✓	14%	26%	60%	15%	28%	57%	6-7	>0,40	>0,70
2062	2322-1037 safari	✓	37%	48%	15%	35%	46%	19%	6-7	>0,45	>0,70
2062	9228-1037 slime grey	✓	32%	33%	35%	30%	31%	39%	6-7	>0,45	>0,70
2062	9229-1037 shadow grey	✓	16%	26%	58%	15%	26%	59%	6-7	>0,45	>0,70
2062	5218-1037 shadow blue	✓	19%	29%	52%	17%	28%	55%	6-7	>0,45	>0,70

All printed colours and textures only provide orientation and are not reference pattern.

Usable for Pleated Blinds
 * Roller / Vertical / Pleated / Panel Track
 Colour Range 8
 Composition 100 % PES
 Width 2250 mm
 Cutting Process hot

Pleating Format 20 mm
 Weight 145 g/m²
 Thickness 0,37 mm
 Damp room usable yes
 PVC free yes
 OekoTex yes



R = Reflection, T = Transmission, A = Absorption • All light & solar properties have been tested internally or externally. • Gtot: measure total solar energy that passes through the glazing system and the fabric • Fc-value: Relation between the total energy transmittance of glazing combined with the sun shading device gtot in combination with total energy transmittance of glazing g • All technical properties are subjected to production-related deviations. All fabrics are in line with the REACH regulation.